



Standard copper tube terminals.

Key features.

- Manufactured from seamless copper tube to BS EN 12449: 2016
- Provided with an inspection hole to ensure the conductor is fully inserted before crimping
- A bell mouth ensures a smooth transition from lug to cable
- The internal barrel diameters suit standard cables as defined in BS6360

Specification.

Material:
Seamless copper tube to
BSEN 12449: 2016

Voltage:
3.3kv

Approvals:
BS EN 61238-1-2003 and BS 4579

Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)								Pack quantity
			A	B	W	E	F	D	L	T	
10	CCT10-5	5	6.6	4.7	10.8	5.6	5.2	4.7	26.0	1.7	1
	CCT10-6	6	6.6	4.7	10.8	5.6	5.2	4.7	26.0	1.7	1
	CCT10-8	8	6.6	4.7	13.5	8.0	7.0	4.7	29.5	1.2	1
	CCT10-10	10	6.9	4.4	16.0	12.0	10.0	4.7	39.0	1.5	1
	CCT10-12	12	6.9	4.4	18.0	12.0	10.0	4.7	39.0	1.2	1
	CCT10-BL	-	6.9	4.4	18.0	12.0	10.0	4.7	39.0	1.2	1
16	CCT16-6	6	7.5	5.5	10.8	8.8	6.2	5.5	30.0	2.0	1
	CCT16-8	8	7.5	5.5	13.5	8.0	7.0	5.5	30.0	1.6	1
	CCT16-10	10	7.5	5.5	15.0	10.9	9.6	5.5	35.5	1.5	1
	CCT16-12	12	8.0	5.6	18.0	12.0	10.0	5.5	42.0	1.3	1
	CCT16-BL	-	8.0	5.6	18.0	12.0	10.0	5.5	42.0	1.3	1
25	CCT25-6	6	9.4	7.0	13.8	8.8	6.2	7.0	32.5	2.4	1
	CCT25-8	8	9.4	7.0	13.8	8.0	7.0	7.0	32.5	2.4	1
	CCT25-10	10	9.4	7.0	16.0	10.9	9.6	7.0	38.0	2.1	1
	CCT25-12	12	9.4	7.0	18.0	10.5	10.0	7.0	38.0	1.9	1
	CCT25-BL	-	9.4	7.0	18.0	10.5	10.0	7.0	38.0	1.9	1

Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)								Pack quantity
			A	B	W	E	F	D	L	T	
35	CCT35-6	6	10.6	8.2	15.3	8.8	6.2	8.2	35.0	2.4	1
	CCT35-8	8	10.6	8.2	15.3	8.0	7.0	8.2	35.0	2.4	1
	CCT35-10	10	10.6	8.2	15.3	10.9	9.6	8.2	40.5	2.4	1
	CCT35-12	12	10.6	8.2	18.0	10.5	10.0	8.2	40.5	2.2	1
	CCT35-BL	-	10.6	8.2	18.0	10.5	10.0	8.2	40.5	2.2	1
50	CCT50-6	6	11.9	9.5	17.4	8.8	6.2	9.5	37.0	2.5	1
	CCT50-8	8	11.9	9.5	17.4	8.0	7.0	9.5	37.0	2.5	1
	CCT50-10	10	11.9	9.5	17.4	10.9	9.6	9.5	42.5	2.5	1
	CCT50-12	12	11.9	9.5	17.4	10.9	9.6	9.5	42.5	2.5	1
	CCT50-BL	-	11.9	9.5	17.4	10.5	10.0	9.5	42.5	2.5	1
70	CCT70-6	6	14.5	11.5	20.9	8.8	6.0	11.5	40.5	3.0	1
	CCT70-8	8	14.5	11.5	20.9	8.0	7.0	11.5	46.0	3.0	1
	CCT70-10	10	14.5	11.5	20.9	10.9	9.6	11.5	46.0	3.0	1
	CCT70-12	12	14.5	11.5	20.9	10.5	10.0	11.5	50.0	3.0	1
	CCT70-14	14	14.5	11.5	20.9	13.0	13.0	11.5	50.0	3.0	1
	CCT70-16	16	14.5	11.5	20.9	13.0	13.0	11.5	50.0	3.0	1
	CCT70-BL	-	14.5	11.5	20.9	13.0	13.0	11.5	50.0	3.0	1
95	CCT95-6	6	16.7	13.5	24.3	10.9	9.6	19.0	49.5	3.2	1
	CCT95-8	8	16.7	13.5	24.3	10.9	9.6	19.0	49.5	3.2	1
	CCT95-10	10	16.7	13.5	24.3	10.9	10.0	19.0	49.5	3.2	1
	CCT95-12	12	16.7	13.5	24.3	10.5	10.8	19.0	49.5	3.2	1
	CCT95-14	14	16.7	13.5	24.3	13.0	13.0	19.0	56.0	3.2	1
	CCT95-16	16	16.7	13.5	24.3	13.0	13.0	19.0	56.0	3.2	1
	CCT95-BL	-	16.7	13.5	24.3	13.0	13.0	19.0	56.0	3.2	1
120	CCT120-8	8	19.0	15.0	27.3	14.4	9.6	20.0	55.5	4.0	1
	CCT120-10	10	19.0	15.0	27.3	14.0	10.0	20.0	55.5	4.0	1
	CCT120-12	12	19.0	15.0	27.2	13.2	10.8	20.0	55.5	4.0	1
	CCT120-14	14	19.0	15.0	27.3	13.0	13.0	20.0	60.0	4.0	1
	CCT120-16	16	19.0	15.0	27.3	13.0	13.0	20.0	60.0	4.0	1
	CCT120-BL	-	19.0	15.0	27.3	13.0	13.0	20.0	60.0	4.0	1
150	CCT150-8	8	21.0	16.5	30.2	14.0	10.0	23.0	61.0	4.5	1
	CCT150-10	10	21.0	16.5	30.2	14.0	10.0	23.0	61.0	4.5	1
	CCT150-12	12	21.0	16.5	30.2	14.0	10.0	23.0	61.0	4.5	1
	CCT150-14	14	21.0	16.5	30.2	13.2	10.8	23.0	61.0	4.5	1
	CCT150-16	16	21.0	16.5	30.2	13.0	13.0	23.0	61.0	4.5	1
	CCT150-BL	-	21.0	16.5	30.2	13.0	13.0	23.0	61.0	4.5	1

Cable size mm ²	Part no.	Stud size (mm)	Dimensions (mm)								Pack quantity
			A	B	W	E	F	D	L	T	
185	CCT185-10	10	23.0	18.5	33.3	15.5	9.2	29.0	66.5	4.5	1
	CCT185-12	12	23.0	18.5	33.3	15.5	9.2	29.0	68.0	4.5	1
	CCT185-14	14	23.0	18.5	33.3	15.5	9.2	29.0	68.0	4.5	1
	CCT185-16	16	23.0	18.5	33.3	13.0	13.0	29.0	70.0	4.5	1
	CCT185-BL	-	23.0	18.5	33.3	13.0	13.0	29.0	70.0	4.5	1
240	CCT240-10	10	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-12	12	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-14	14	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-16	16	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-20	20	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
	CCT240-BL	-	26.0	21.0	37.7	18.0	17.0	32.0	88.0	5.0	1
300	CCT300-10	10	28.0	23.0	41.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-12	12	28.0	23.0	41.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-14	14	28.0	23.0	41.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-16	16	28.0	23.0	41.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-20	20	28.0	23.0	41.0	18.0	17.0	37.0	97.0	5.0	1
	CCT300-BL	-	28.0	23.0	41.0	18.0	17.0	37.0	97.0	5.0	1
400	CCT400-10	10	32.0	27.0	47.3	22.0	22.0	38.0	108.0	5.0	1
	CCT400-12	12	32.0	27.0	47.3	22.0	22.0	38.0	108.0	5.0	1
	CCT400-14	14	32.0	27.0	47.3	22.0	22.0	38.0	108.0	5.0	1
	CCT400-16	16	32.0	27.0	47.3	22.0	22.0	38.0	108.0	5.0	1
	CCT400-20	20	32.0	27.0	47.3	22.0	22.0	38.0	108.0	5.0	1
	CCT400-BL	-	32.0	27.0	47.3	22.0	22.0	38.0	108.0	5.0	1
500	CCT500-10	10	36.0	30.0	53.0	28.0	24.0	38.0	117.0	6.9	1
	CCT500-12	12	36.0	30.0	53.0	28.0	24.0	38.0	117.0	6.9	1
	CCT500-14	14	36.0	30.0	53.0	28.0	24.0	38.0	117.0	6.9	1
	CCT500-16	16	36.0	30.0	53.0	28.0	24.0	38.0	117.0	6.9	1
	CCT500-20	20	36.0	30.0	53.0	28.0	24.0	38.0	117.0	6.9	1
	CCT500-BL	-	36.0	30.0	53.0	28.0	24.0	38.0	117.0	6.9	1