

Rittal – The System.

Faster – better – everywhere.

► Hygienic Design Compact enclosure HD, single-door – HD 1320.600

Date : Feb 21, 2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Hygienic Design Compact enclosure HD, single-door – HD 1320.600

created: 21.02.2020 build on www.rittal.com/uk-en



Product description

Design:	Roof angled forwards by 30°
Material:	Enclosure and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Sheet steel Lock insert HD: Stainless steel 1.4404 (AISI 316L) Seal: Silicone, compliant with FDA Guideline 21 CFR 177.2600
Surface finish:	Enclosure and door: Brushed, grain 400, peak-to-valley height < 0.8 µm Mounting plate: Zinc-plated Seal: Blue, dyed (RAL 5010)
Protection category IP to IEC 60 529:	IP 66 IP X9
Protection category IP to DIN 40 050-9:	IP 69K
Protection category NEMA:	NEMA 13 NEMA 4X
IK Code:	IK08
Supply includes:	Enclosure of all-round solid construction Door with inserted seal Door hinged on the right, may be swapped to the left Mounting plate
Basic material:	Stainless steel

Product features

Dimensions:	Width: 610 mm Height (front): 430 mm Height rear: 601 mm Depth: 300 mm
Mounting plate:	Width: 549 mm Height: 355 mm
Door opening angle:	125°
Number of cam locks:	2
Packs of:	1 pc(s).
Weight/pack:	21.7 kg
EAN:	4028177567665
Customs tariff number:	94032080
ETIM 7.0:	EC000261
ETIM 6.0:	EC000261
eCl@ss 8.0/8.1:	27180101
eCl@ss 6.0/6.1:	27180101
Product description:	HD Compact enclosure, WHD: 610x430(H1)x601(H2)x300 mm, Stainless steel 1.4301, with mounting plate, with hinged door and silicone seal
Approvals	
Approvals:	UL + C-UL
Certificates:	EAC Protection category
Declarations:	Declaration of conformity