



LQMAEC-303SS

▶ DOUBLE-ENDED CORDSETS



WLB AC Quick Disconnect Cable
Double-ended 3-pin Female Connector Straight
4-pin Female Connector Straight
Length 0.91 m
Part Number: 85579

CERTIFICATIONS



SPECIFICATIONS

Number of Contacts	3
Number of Connectors	2
Cable Jacket Material	PVC
Cable Jacket Color	Black
Connector Body Material/Color	PVC Black
Outside Cable Diameter (mm)	6.8
Cordset Length (m)	0.91
Trunk Length (m)	No Trunk
Shield/No Shield	No Shield
Coupling Material/Color	Nylon
Maximum Temp. (°C)	105
Current Rating (A)	3.0
Minimum Temp. (°C)	-40
Voltage Rating (V)	300 V ac/dc
IP Rating	IP50
Primary Connector Type	Molex
Primary Coupling Method	Slide Snap
Primary Gender	Male
Primary Orientation	Straight
Primary Number of Conductors	3
Primary AWG	18
Secondary Connector Type	Molex
Secondary Coupling Method	Slide Snap
Secondary Gender	Male
Secondary Orientation	Straight
Secondary Number of Conductors	4
Secondary AWG	18
Feature: Hazardous Area	No
Oil/Grease Resistant	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America

By accepting cookies, we give you the best experience throughout our site, including access to My Account, My Library, and My Wish List.

To learn more, visit our [privacy policy](#).