



Digital enclosure internal temperature display and thermostat – SK 3114.200

Date : Jun 4, 2020



Digital enclosure internal temperature display and thermostat – SK 3114.200

: 04.06.2020 build on www.rittal.com/uk-en



Product description

Description: For installation in the enclosure door or wall.

Technical specifications: Three-digit, 7-segment display
Option of switching between °C/°F
Includes 1800 mm long NTC sensor
Two relay outputs as change-over contact and normally open contact (max. contact load 230 V, 6 A)
Freely selectable switching difference

Colour: RAL 7035

**Protection category
IP to IEC 60 529:** IP 54

Product features

**Rated operating
voltage:** 100 V - 230 V, 1~, 50 Hz/60 Hz
24 V - 60 V (DC)

Installation depth: 100 mm

Temperature range: Operation (environment): +0 °C...+50 °C
Setting range: +5 °C...+55 °C

Packs of: 1 pc(s).

Weight/pack: 0.26 kg

EAN: 4028177631434

Customs tariff number:	90321020
ETIM 7.0:	EC002014
ETIM 6.0:	EC002014
eCl@ss 8.0/8.1:	27210707
eCl@ss 6.0/6.1:	27210707
Product description:	SK Digital enclosure internal , temperature display and thermostat, 100-230 V, 1~, 50/60 Hz, 24-60 V (DC), Installation depth: 100 mm
Approvals	
Approvals:	CCC exception letter UR
Certificates:	EAC
Declarations:	Declaration of conformity