

Screwdrivers	440
Torque screwdrivers	442
Pliers	444
Cable cutters	444
Stripping tools	445
Crimping tools	445
Voltage testers	447
Neoprene sleeve expander tools	448





SlimLine, thin blade VDE insulated screwdrivers **Weidmüller** 

3-year warranty

Features

- Ideal for working on live parts up to 1,000V a.c. and 1,500V d.c. DIN EN60900, IEC 900, safety tested.
- Insulation is 33% thinner than standard VDE insulated screwdrivers
- Ergonomic SoftFinish® grip for optimum handling
- Hardened gun metal chrome-vanadium steel shafts.

Dimensions (mm)

VDE insulated screwdrivers protect you when working on live parts, but the insulation can be too thick to reach deeply inset fittings.

The blade insulation on Weidmüller SlimLine screwdrivers is up to 33% thinner, allowing you to reach deeply inset fittings & tension clamp terminals which cannot normally be reached using a standard VDE screwdriver.

Slot head VDE-insulated SlimLine screwdrivers

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Slot head screwdriver	0.6	3.5	100	1274660000	£6.95
Slot head screwdriver	0.8	4	100	1274670000	£8.28
Slot head screwdriver	1	4.5	125	1274680000	£10.03
Slot head screwdriver	1.2	6.5	150	1274690000	£12.92

Phillips VDE-insulated SlimLine screwdrivers

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Phillips PH1 screwdriver	4.5	4.5	80	1274710000	£9.19
Phillips PH2 screwdriver	6	6	100	1274720000	£12.33

6 piece VDE-insulated SlimLine screwdriver set

Description	Order Code	List Price
VDE insulated screwdriver set (the 6 screwdrivers listed above)	1274750000	£42.24

Pozidriv VDE-insulated SlimLine screwdrivers

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Pozidriv PZ1 screwdriver	4.5	4.5	80	1274730000	£10.19
Pozidriv PZ2 screwdriver	6	6	100	1274740000	£13.91



Do you place your orders online?

We can help with that ...

www.lcautomation.com

Standard blade VDE insulated screwdrivers




3-year warranty

VDE insulated screwdrivers are suitable for use in applications up to 1000V a.c. and offer fully hardened high alloy steel blades in a black gunmetal finish.

The ergonomically designed handles enable fatigue-free, comfortable working and the SoftFinish® zone ensures optimum 'slip-free' control for high torque tightening and loosening of screws.

Features

- Ideal for working on live parts up to 1,000V a.c. and 1,500V d.c. DIN EN60900, IEC 900, safety tested
- Ergonomic SoftFinish® grip for optimum handling
- Hardened gun metal chrome-vanadium steel shafts



Slot head VDE-insulated screwdrivers

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Slot head screwdriver	0.4	2.5	75	9008370000	£5.06
Slot head screwdriver	0.5	3	100	9008380000	£5.13
Slot head screwdriver	0.8	4	100	9008400000	£6.22
Slot head screwdriver	1	5.5	125	9008410000	£7.62

Phillips VDE-insulated screwdrivers

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Phillips PH1 screwdriver	4.5	4.5	80	1318330000	£8.37
Phillips PH2 screwdriver	6	6	100	1318340000	£10.28

6 piece VDE-insulated screwdriver set

Description	Order Code	List Price
VDE insulated screwdriver set (the 6 screwdrivers listed above)	9009730000	£25.66

Pozidriv VDE-insulated screwdrivers

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Pozidriv PZ1 screwdriver	4.5	4.5	80	9008900000	£7.20
Pozidriv PZ2 screwdriver	6	6	100	9008890000	£8.69

Non-insulated screwdrivers



Angled slotted screwdriver with rounded blade, chrome top tip and SoftFinish® grip.



3-year warranty

Torx® handled screwdriver

Common technical specification

- Classifications
 eClass 6.0 21-04-04-01
 eClass 7.0 21-04-04-90
 GTIN (EAN) 4050118127133

Angled slot head screwdriver

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Angled slot head screwdriver	0.6	3	70	1323880000	£6.05

Torx handled screwdrivers

Description	Dimensions (mm)			Order Code	List Price
	Thick (A)	Wide (B)	Long (C)		
Torx T15 handled screwdriver	3.27	3.27	100	1318390000	£6.64
Torx T20 handled screwdriver	3.86	3.86	100	1318400000	£7.05
Torx T40 handled screwdriver	6.65	6.65	100	1318410000	£7.46

VDE insulated torque screwdriver

Weidmüller


Setting tool (included)

Manual torque screwdriver with an integral window scale, and when combined with the insulated blades below, ensures controlled tightening of screws and maximum reliability in electrical applications.

Available in two torque ranges:

- 0.5 to 1.7 Nm
- 2.0 to 8.0 Nm

Technical specification

Protection 1,000V a.c./1,500V d.c.

Torque range 0.5 - 1.7 Nm
2.0 - 8.0 Nm

Accuracy Standards EN ISO 6798,
BS EN 26789
ASME B107.14M

Features

- Tested to provide the necessary safety up to 1,000V a.c./1,500V d.c.
- Includes torque setting tool to ensure the correct setting
- Ergonomic handle size to match the torque range
- Audible, unmistakable click upon reaching the torque

Description	Order Code	List Price
Insulated torque screwdriver; 0.5-1.7 Nm version	9918390000	£135.83
Insulated torque screwdriver; 2 - 8 Nm version	9918400000	£150.74

Interchangeable bits for VDE insulated torque screwdriver

Weidmüller

A range of interchangeable Slot Head, Phillips and Pozidriv bits for use with the VDE insulated torque screwdriver above.

Suitable for effective and exact work this precise torque guarantees high repetition accuracy, with maximum reliability in electrical applications.

Technical specification

Protection 1,000V a.c./1,500V d.c.

Torque range see price box

Accuracy Standards EN ISO 6798,
BS EN 26789
ASME B107.14M



Slot head VDE-insulated interchangeable bits

Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Slot head bit	0.4 Nm	0.4	2.5	200	9918410000	£6.37
Slot head bit	0.6 Nm	0.5	3	200	9918420000	£6.37
Slot head bit	1.1 Nm	0.6	3.5	200	9918430000	£6.37
Slot head bit	2.5 Nm	0.8	4	200	9918440000	£6.37
Slot head bit	3.8 Nm	1	5.5	200	9918450000	£6.37


Phillips VDE-insulated interchangeable bits

Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Phillips PH0 Bit	3.8 Nm	3	3	200	9918470000	£6.37
Phillips PH1 Bit	5.5 Nm	4.5	4.5	200	9918480000	£6.37
Phillips PH2 Bit	9 Nm	6	6	200	9918460000	£6.37

Pozidriv VDE-insulated interchangeable bits

Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Pozidriv PZ0 Bit	3.8 Nm	3	3	200	9918490000	£6.37
Pozidriv PZ1 Bit	5.5 Nm	4.5	4.5	200	9918500000	£6.37
Pozidriv PZ2 Bit	9 Nm	6	6	200	9918510000	£6.37

Dimensions (mm)



Torque screwdriver with rechargeable battery



3-year warranty

Features

- One-hand operation under all working conditions
- Clockwise/anticlockwise
- Precise torque selection from 0.4 - 3Nm in 6 steps
- Includes carry case, battery, charger and interchangeable bit set
 - Safety lock prevents unintentional activation
 - Simple switchover from battery to manual operation (up to 15Nm)

Technical specification

Torque range0.4 - 3Nm
Rated voltage2.4 V
BatteryNi-Cd, 1.2 V
Charging time1 hour
Bit holder1/4" DIN 3126 (form E6.3)
Screwdriver weight400g

Description	Order Code	List Price
Battery operated torque screwdriver set	9007470000	£288.39
Battery operated torque screwdriver set (with additional battery)	9007480000	£346.87

Weidmüller torque screwdrivers have an ergonomic design, ideal for using with one hand.

Battery powered screwdrivers can reduce fatigue in any installation. They also incorporate an automatic torque limiter.

Slot head interchangeable bits

Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Slot Head Bit	0.4 Nm	0.4	2.5	70	9202750000	£5.88
Slot Head Bit	0.6 Nm	0.5	3	70	9024000000	£5.88
Slot Head Bit	1.1 Nm	0.6	3.5	70	9024020000	£5.88
Slot Head Bit	2.5 Nm	0.8	4	70	9024030000	£5.88
Slot Head Bit	3.8 Nm	1	5.5	70	9024040000	£5.88
Slot Head Bit	4.2 Nm	1.2	6.5	70	9202740000	£5.88

Interchangeable bits



Features:

- Suitable for use with both manual and power tools
- Consistently high quality with good wearing resistance
- Optimum torque transmission

Phillips interchangeable bits

Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Phillips PH1 Bit	5.5 Nm	4.5	4.5	70	9024080000	£3.89
Phillips PH2 Bit	9 Nm	6	6	70	9024090000	£3.89

Pozidriv interchangeable bits


Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Pozidriv PZ1 Bit	5.5 Nm	4.5	4.5	70	9024100000	£3.89
Pozidriv PZ2 Bit	9 Nm	6	6	70	9024110000	£3.89

Pilot tip interchangeable bits

Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Pilot Tip Bit	1.1 Nm	0.6	3.5	70	9205670000	£8.69
Pilot Tip Bit	2.5 Nm	0.8	4	70	9205660000	£8.69

Torx interchangeable bits

Description	Maximum Torque	Dimensions (mm)			Order Code	List Price
		Thick (A)	Wide (B)	Long (C)		
Torx T15 Bit	7.7Nm	3.27	3.27	70	1318350000	£5.72
Torx T20 Bit	12.7Nm	3.86	3.86	70	1318370000	£5.72
Torx T40 Bit	65Nm	6.65	6.65	70	1318380000	£5.72



VDE insulated pliers and side cutters

Weidmüller 


Combination pliers



Long nose pliers

**3-year
warranty**


Stripping Pliers



Side cutters

A range of pliers that have been specially produced and tested for working with live voltages.

They comply with national and international testing standards. All pliers are produced and tested according to DIN EN 60900.

They are ergonomically designed to fit to the hand, resulting in less fatigue during operation.

Features

- 160mm handle
- 1,000V VDE tested
- High quality, drop forged steel
- Safety handle with ergonomic soft finish non-slip VDE grip
- Shockproof, heat and cold resistant insulation
- Nickel chromium electro coating protects against corrosion

Description	Order Code	List Price
Combination pliers	9046280000	£17.40
Long nose pliers	9046370000	£18.22
Stripping pliers	9046440000	£17.40
Side cutters	9046320000	£20.71

Cable cutters

Weidmüller 


KT22

**3-year
warranty**


KT55

KT series cutters can cut small cross section cables all the way up to ratchet cable cutters for larger copper cables up to 630mm².

They all feature mechanical operation and specially designed cutter shapes, which minimise the effort required.

Features include

- Cuts without crushing or deformation of the conductor
- Maximum cutting capacity (stranded copper conductors)
 - KT8 Up to 16mm²
 - KT12 Up to 25mm²
 - KT14 Up to 35mm²
 - KT22 Up to 50mm²

Ratchet version features

- Easy handling
- Minimal hand force required
- Release option in every cutting position
- Maximum cutting capacity
 - KT45R Up to 300mm²
 - KT55 Up to 500mm²
 - KT80 Up to 630mm²

KT series cable cutters

Description	Max Cutting Capacity	Order Code	List Price
KT8 cable cutters	16mm ²	9002650000	£22.37
KT12 cable cutters	25mm ²	9002660000	£24.52
KT14 cable cutters	35mm ²	1157820000	£29.48
KT22 cable cutters	50mm ²	1157830000	£32.96

KT series ratchet cable cutters

Description	Max Cutting Capacity	Order Code	List Price
KT45R ratchet cable cutters	300mm ²	9202040000	£193.79
KT55 ratchet cable cutters	500mm ²	9202060000	£266.68
KT80 ratchet cable cutters	630mm ²	9202080000	£556.53

Sheath stripper

Weidmüller 

3-year warranty

Features

- Pivoting blade for circular, spiral and longitudinal cutting of hard insulation
- For 6 to 25mm² diameter cables
- Adjustable cutting depth (maximum 4.5mm)
- The blade in the retaining clip breaks open an incision in the insulation
- Blade can easily be replaced and a spare is included (in the handle)
- For PVC-insulated round cable, ribbon cable or UTP and STP data cables
- Can also be used to remove cut insulation

Description	Order Code	List Price
AM25 sheath stripper; for 6 - 25mm ² cable	9001540000	£28.15

Professional cable stripping tool

Weidmüller 

3-year warranty

Poor quality or inconsistent stripping of the insulation from conductors can result in:

- Damaged conductor insulation
- Insulation left on the stripped area
- Strands being damaged or cut off and reducing the cable cross section

Any of these problems can result in an unsafe electrical connection and possible overheating.

Features

- For flexible and solid conductors with PVC insulation 0.08mm² to 16mm²
- Stripping and cutting with one tool
- Automatic opening of clamping jaws after stripping
- Stripping length is adjustable via the end stop
- Adjustable for different insulation thicknesses
- No damage of single conductors
- Optimised ergonomic design

Stripax® saves time by stripping and cutting insulation and sheathing, with just one tool. It also provides consistent stripping which helps ensure a safe electrical connection.

Description	Order Code	List Price
Stripax stripping tool; for 0.08 - 10mm ² cable	9005000000	£59.63
Stripax stripping tool; for 6 - 16mm ² cable	9005610000	£91.11

Professional cable stripping and crimping tool

Weidmüller 

3-year warranty

For the first time wire can be prepared, ready for connection with just one tool. It really comes into its own when used in overhead or awkward positions, where it can be difficult to repeatedly swap the tools that you are using.

Features

- Cutting, stripping and crimping with just one tool
- For use with linked bootlace ferrules from 0.5 to 2.5mm² (listed below)
- Ratchet for precise crimping
- Dial adjustment for different sizes

Description	Order Code	List Price
Stripax Plus 2.5 for linked bootlace ferrules; 0.5 - 2.5mm ²	9020000000	£212.03

Stripax® Plus 2.5 combines cutting, stripping and crimping in just one tool! Easy and straightforward, it uses linked bootlace ferrule strips (up to 2.5mm²) to dramatically reduce installation time.

Linked bootlace ferrule strips for Stripax Plus 2.5

Size	Pack size	Colour	Order Code	List Price
0.5mm ²	500 pieces	Orange	9004270000	£15.24
0.75mm ²	500 pieces	White	9004290000	£15.24
1mm ²	500 pieces	Yellow	9004320000	£15.00
1.5mm ²	500 pieces	Red	9004340000	£15.30
2.5mm ²	500 pieces	Blue	9004360000	£17.08

Rotary bootlace ferrule crimping tool

Weidmüller


3-year warranty

The PZ 6 Roto is ideal for crimping in hard to reach places, with a rotating die which can accept ferrules from either side or front.

No need to change tools

With just one tool, you can crimp cables and wire ferrules over the complete cross-section range from 0.14 to 6mm².

Rotary crimping insert

The rotary crimping insert allows you to insert the wire-end ferrules either from the front or side.

Lockable crimp insert

The lockable crimp insert, combines the flexibility of a rotary tool, with the reliability of a fixed die.

Features

- Rotating die enables bootlace ferrule to be inserted from the front or side
- For bootlace ferrules with and without plastic collars, according to DIN 46228 T.1 and T.4
- Only one die for the whole cross section range from 0.14 to 6mm²
- Ratchet for precise crimping
- Release option in the event of incorrect operation

Description	Order Code	List Price
PZ 6 Roto bootlace crimping tool; 0.14 - 6mm ²	9014350000	£122.58

Crimping tool for insulated crimps

Weidmüller


3-year warranty

The Weidmüller CTI 6 provides reliable crimping of insulated connectors from 0.5 to 6mm².

Its major advantage is that it has a double crimp profile, which crimps the contact and insulation in one step.

Features

- For PVC, PC and polyamide insulated connectors from 0.5 to 6mm²
- Double crimp profile, for crimping contact and insulation in one step
- Ratchet for precise crimping
- Release option in the event of incorrect operation
- With stop for exact positioning of crimps

Description	Order Code	List Price
CTI 6 crimping tool for insulated crimps; 0.5 - 6mm ²	9006120000	£122.58

Assorted bootlace ferrules with plastic collars

Weidmüller



Features

- Polypropylene conical cable entry funnel
- Heat-resistant up to 105°C
- For conductors from 0.14 to 16 mm²

- Material: E-Cu, tin galvanised
- Dimensional tolerance according to DIN 46228 sect. 4

Size	Pack size	Colour Code	Order Code	List Price
0.14 - 0.75mm ²	1 assorted box	Weidmüller	9025410000	£17.40
0.5 - 2.5mm ²	1 assorted box	Weidmüller	9025900000	£23.45
4 - 16mm ²	1 assorted box	Weidmüller	9025920000	£25.59
0.5 - 2.5mm ²	1 assorted box	DIN	9025430000	£24.14
4 - 16mm ²	1 assorted box	DIN	9025400000	£17.78

Ratchet action tool for cord end terminals



Ratchet action crimp tool for cord end terminals from 0.14 to 50mm².

Description	Order Code	List Price
Ratchet action crimp tool; 0.14 - 2.5mm ²	CRT0.14-2.5	£26.98
Ratchet action crimp tool; 0.25 - 6mm ²	CRT0.25-6.0	£38.53
Ratchet action crimp tool; 6 - 16mm ²	CRT6-16	£35.64
Ratchet action crimp tool; 10 - 25mm ²	CRT10-25	£35.64
Ratchet action crimp tool; 10 - 35mm ²	CRT10-35	£40.07
Ratchet action crimp tool; 25 - 50mm ²	CRT25-50	£38.53

Crimping tool for pre-insulated terminals



Budget crimp tool with a single cast multi-die head that is suitable for pre-insulated terminals from 0.5 to 6mm².

Description	Order Code	List Price
Crimping tool; 0.5 - 6mm ²	CRT123B	£22.00

Two pole voltage testers



The Weidmüller range of two pole voltage testers are used for proving the absence of voltage which is recommended by the Health and Safety Executive in HSE guidance note GS38.

All testers are TUV/GS certified and meet the revised standards for these type of testers i.e DIN VDE 0682-401: 2001 I and DIN EN-61243-3:2010.

Features

- HSE GS38 compliant (2mm probes)
- CAT IV – 600V
- IP 65 protection
- TUV/GS certified
- Temperature resistant -15 to +45°C
- Large display
- Illumination LED

Common technical specification

Protection rating	IP65
Operating temperature	-15 to +45°C
Power supply	2 x 1.5V AAA
Category	CAT IV - 600V CAT III - 690V

Description	Rated Voltage Range	Display	Continuity Test	Single pole phase test	Illuminated measuring probes	Hold Function	Phase Sequence Indicator	Switchable Load	30mA RCD Trigger	Order Code	List Price
Master check	6-400V	LED	●	–	–	–	–	–	–	9201260000	£33.13
Combi check	6-400V	LED	●	●	–	–	●	–	–	9204230000	£43.07
Multi check	5-500V	Digital LCD	●	●	–	●	–	–	–	9201570000	£49.92
Digi check	5-500V	Digital LCD	●	●	●	●	–	–	–	9201590000	£94.03
Digi check pro	5-500V	Digital LCD	●	●	●	●	●	●	●	9201580000	£98.09

Neoprene sleeve expander tools



A range of four high quality ultra lightweight tools ensure speedy application. They can be used for fitting neoprene sleeves with internal diameters up to 20mm.

Technical specification

Operating temperature . . . 10 to 150°C
 Standards AFS NO. 61 1A;
 DTD 900/4877

To suit internal diameter	Order Code	List Price
1.2-2.5mm (CH12-CH20)	KY1	£36.00
2.5-5mm (CH20-CH50)	KY2	£36.00
3-10mm (CH30-CH100)	KY3	£36.00
10-20mm (CH100-CH200)	KY4	£36.00



KY1– to suit 1.2-2.5mm (CH12-CH20)



KY2– to suit 2.5-5mm (CH20-CH50)



KY3– to suit 3-10mm (CH30-CH100)



KY4– to suit 10-20mm (CH100-CH200)

