

Polycarbonate enclosures PK



PK accessories Page 47 System accessories Page 877 Cable gland, polyamide Page 1056

Applications:

- Ambient temperature range: -35 °C...+80 °C
- The specified temperatures may be limited by the installed equipment

Material:

- Enclosure: Fibreglass reinforced polycarbonate
- Cover grey: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal
- Cover transparent: Polycarbonate, all-round foamed-in PU seal
- Cover screws: Polyamide
- Insulating bungs: Polyethylene

Colour:

- RAL 7035

Protection category IP to IEC 60 529:

- IP 66

Protection category NEMA:

- NEMA 4X

Supply includes:

- Enclosure with cover
- Cover screws
- Insulating bungs for wall mounting screws

Approvals:

- UL
- cUL
- DNV GL

without knockouts

Width mm		65	94	94	94	110	110	Page
Height mm		65	65	94	94	110	110	
Depth mm		57	57	57	81	66	90	
Model No.		9500.000	9502.000	9504.000	9505.000	9506.000	9507.000	
	Packs of	12 pc(s).	8 pc(s).	6 pc(s).	6 pc(s).	6 pc(s).	6 pc(s).	
Cover	grey	■	■	■	■	■	■	
Accessories								
Mounting plate		-	-	-	-	-	-	
Hinge		-	-	-	-	-	-	
Wall mounting bracket	40 pc(s).	9583.000	9583.000	9583.000	9583.000	9583.000	9583.000	47

without knockouts

Width mm		130	130	130	130	180	180	Page
Height mm		94	94	130	130	94	94	
Depth mm		57	81	75	99	57	81	
Model No.		9508.000	9509.000	9510.000	9511.000	9512.000	9513.000	
	Packs of	4 pc(s).	4 pc(s).	4 pc(s).	4 pc(s).	2 pc(s).	2 pc(s).	
Cover	grey	■	■	■	■	■	■	
Accessories								
Mounting plate		-	-	-	-	-	-	
Hinge		-	-	-	-	-	-	
Wall mounting bracket	40 pc(s).	9583.000	9583.000	9583.000	9583.000	9583.000	9583.000	47

Polycarbonate enclosures PK

without knockouts

Width mm	Packs of	180	180	180	180	180	180	Page
Height mm		110	110	110	110	110	110	
Depth mm		90	90	111	111	165	165	
Model No.	2 pc(s).	9514.000	9514.100	9515.000	9515.100	9516.000	9516.100	
Cover	grey	■	–	■	–	■	–	
	transparent	–	■	–	■	–	■	
Accessories								
Mounting plate		–	–	–	–	–	–	
Hinge	20 pc(s).	9581.000	9581.000	9581.000	9581.000	9581.000	9581.000	47
Wall mounting bracket	40 pc(s).	9583.000	9583.000	9583.000	9583.000	9583.000	9583.000	47

without knockouts

Width mm	Packs of	182	182	182	182	182	182	Page
Height mm		180	180	180	180	180	180	
Depth mm		90	90	111	111	165	165	
Model No.	1 pc(s).	9517.000	9517.100	9518.000	9518.100	9519.000	9519.100	
Cover	grey	■	–	■	–	■	–	
	transparent	–	■	–	■	–	■	
Accessories								
Mounting plate	10 pc(s).	9548.000	9548.000	9548.000	9548.000	9548.000	9548.000	47
Hinge	20 pc(s).	9581.000	9581.000	9581.000	9581.000	9581.000	9581.000	47
Wall mounting bracket	40 pc(s).	9583.000	9583.000	9583.000	9583.000	9583.000	9583.000	47

without knockouts

Width mm	Packs of	254	254	254	254	254	254	Page
Height mm		180	180	180	180	180	180	
Depth mm		90	90	111	111	165	165	
Model No.	1 pc(s).	9520.000	9520.100	9521.000	9521.100	9522.000	9522.100	
Cover	grey	■	–	■	–	■	–	
	transparent	–	■	–	■	–	■	
Accessories								
Mounting plate	8 pc(s).	9549.000	9549.000	9549.000	9549.000	9549.000	9549.000	47
Hinge	20 pc(s).	9581.000	9581.000	9581.000	9581.000	9581.000	9581.000	47
Wall mounting bracket	40 pc(s).	9583.000	9583.000	9583.000	9583.000	9583.000	9583.000	47

without knockouts

Width mm	Packs of	360	360	360	360	360	360	Page
Height mm		254	254	254	254	254	254	
Depth mm		111	111	165	165	165	165	
Model No.	1 pc(s).	9523.000	9523.100	9524.000	9524.100	9524.100	9524.100	
Cover	grey	■	–	■	–	■	–	
	transparent	–	■	–	■	–	■	
Accessories								
Mounting plate	4 pc(s).	9550.000	9550.000	9550.000	9550.000	9550.000	9550.000	47
Hinge	20 pc(s).	9581.000	9581.000	9581.000	9581.000	9581.000	9581.000	47
Wall mounting bracket	40 pc(s).	9583.000	9583.000	9583.000	9583.000	9583.000	9583.000	47

Polycarbonate enclosures PK



PK accessories Page 47 System accessories Page 877 Cable gland, polyamide Page 1056

Applications:

- Ambient temperature range: -35 °C...+80 °C
- The specified temperatures may be limited by the installed equipment

Material:

- Enclosure: Fibreglass reinforced polycarbonate
- Cover: Fibreglass-reinforced polycarbonate, all-round foamed-in PU seal
- Cover screws: Polyamide
- Insulating bungs: Polyethylene

Colour:

- RAL 7035

Protection category IP to IEC 60 529:

- IP 66

Protection category NEMA:

- NEMA 4X

Supply includes:

- Enclosure with cover
- Cover screws
- Insulating bungs for wall mounting screws

Approvals:

- UL
- cUL
- Bureau Veritas

with knockouts

Width mm		130	180	254	Page
Height mm		94	110	180	
Depth mm		57	90	111	
Model No.		9508.050	9514.050	9521.050	
	Packs of	4 pc(s).	2 pc(s).	1 pc(s).	
Cover	grey	■	■	■	
No. of metric knockouts		10 x M16/M20	16 x M20 2 x M20/M25 2 x M32/M40	24 x M20 4 x M25/M32 4 x M32/M40	
Accessories					
Mounting plate	8 pc(s).	-	-	9549.000	47
Wall mounting bracket	40 pc(s).	9583.000	9583.000	9583.000	47

Polycarbonate enclosures PK

Accessories

Mounting plate

for PK

For individual interior installation.

Material:

- 2.5 mm melamine phenol-coated laminated paper

Colour:

- RAL 7035

Supply includes:

- Mounting plate
- Self-tapping assembly screws

Mounting plate width mm	Mounting plate height mm	For enclosure width mm	For enclosure height mm	Packs of	Model No.
150	150	182	180	10 pc(s).	9548.000
220	150	254	180	8 pc(s).	9549.000
331	220	360	254	4 pc(s).	9550.000

Hinge

for PK

For hinged attachment of covers. The supplied drilling template ensures problem-free assembly.

Material:

- Polystyrene

Colour:

- Similar to RAL 7035

Supply includes:

- 20 hinges
- Assembly parts

For enclosure width mm	For enclosure height mm	Material	Packs of	Model No.
≥ 180	≥ 110	Polystyrene	20 pc(s).	9581.000

Wall mounting bracket

for PK

The enclosure can be screwed to the wall using four wall mounting brackets. The bracket is securely attached to the enclosure by means of pins.

Applications:

- For all PK enclosures

Material:

- Polyamide, grey

Colour:

- Similar to RAL 7035

Packs of	Model No.
40 pc(s).	9583.000

